

Addendum

Bid Identification No: - MPTRADECO / ADB / IABS

ICB No: - MPTRADECO/ADB/ICB/2010/01

Procurement of Integrated Automated Business Solution & related Services for MP Trade Co.

No: - MP Tradeco/CGM(S)/IABS/Procure/Addendum//067 Jabalpur Dtd: - 07-09-2010

Section, Page, Clause No of Bid Document	Statement/Clause as appearing in the Bid Document	Details of Modification / Addition
II, 9,ITB 38 (v)	The Financial evaluation shall not be done on basis of Net Present value. The cost as quoted by the Bidder for expenditure during the Manage IT period for five year shall be considered without any adjustment.	<p>To be read as: "The Financial evaluation shall not be done on basis of Net Present value. The cost as quoted by the Bidder for expenditure during the Manage IT period for four years shall be considered without any adjustment"</p>
III, 23,2.6	"Sub Contractors"	<p>The current clause " sub contractors", is appended with the following, "5. supply of bandwidth from ISP's with Category A license and operational in State of Madhya Pradesh for at least 2 Year at the time of Bid Opening"</p>
IV,31,5.1	5.1 Bid Security (Bank Guarantee)	<p>The current clause "Bank security " is appended with the following clause "Not withstanding anything contained herein above. Our liability under this bank guarantee shall not exceed Rs _____/- (Rupees _____ only). This bank guarantee shall be valid upto _____ We are liable to pay the guaranteed amount or any part thereof under this bank guarantee only if you serve upon us a written claim or demand (and which should be received by us), on or before _____ before 14.30 hours (Indian Standard Time) where after it ceases to be ineffective in all respects whether or not the original bank guarantee is returned to us."</p>

IV, 32, 5.2	5.2 Manufacturer's Authorization"- 4. As OEM we assure the Employer of this bid that we shall verify the product after installation prior to 'Go-Live' and certify successful implementation of the solution as per the OEM standards and the requirements as specified in this Bidding Document	Point 4 of Manufacturer's Authorization to be read as: - "4. OEM shall declare that OEM and SI have entered into a formal relationship in which, during the execution of the Contract, OEM shall provide assistance to resolve technical issues during the customization/ integration/ development of the..... by way of providing resources on time and material basis from the date of subcontract between SI and OEM."
IV,36,6.1 b (4)	<ul style="list-style-type: none"> • Non existent 	Third party application audit by STQC or through a vendor selected by the employer from those empanelled with NIC / CERT-in / Govt of India / Govt of MP at SI cost.
VI,9,J	<ul style="list-style-type: none"> • Certificate from OEM of the COTS product for successful implementation 	Stands deleted
VI, 40, 5.2(3)	Unless otherwise specified, all equipment must operate in environments of. 10-46 degree centigrade, 20-90 percent relative humidity, and 0-40 grams per cubic meter of dust.	To be read as: Unless otherwise specified, all equipment (The Servers, SAN Storages, Tape Library etc.) must operate in environments of. 10-35 degree centigrade, 20-70 percent relative humidity, and 0-40 grams per cubic meter of dust. Conditioned, De-humidified and Dust controlled environment.
VI, 47,XXI	Application software implementation should be certified by COTS OEM vendor for successful implementation	To be read as. The bidder has to get the application audited through a third party chosen by the Employer. The acceptance of the application would be post satisfactory third party audit. The audit would be done by STQC of through a vendor selected by the employer from those empanelled with NIC / CERT-in / Govt of India / Govt of MP at SI cost
VII, 11,65.1	The selected vendor shall ensure verification and certification from the OEM prior to 'Go-Live' for successful implementation of the solution as per the OEM standards and the requirements as specified in this Bidding Document	Deleted
VIII,11,65.1	65.1 The selected Vendor shall ensure verification and certification from the OEM prior to Go-Live for successful implementation of the solution as per the OEM standards and the requirements as specified in this bidding document	To be read as: The bidder has to get the application audited through a third party chosen by the Employer. The acceptance of the application would be post satisfactory third party audit. The audit would be done by STQC of through a vendor selected by the employer from those empanelled with NIC / CERT-in / Govt of India / Govt of MP at SI cost

VIII,11,65.3	Non existent	Added as follows: - 65.3 Where successful bidder has arrangement with OEM for getting resources on time and material basis for the purpose of development / customization / implementation of their product, and if the SI fails to avail the resources from OEM on time / Employer's request then the Employer shall have the right to call the OEM resources on SI cost and responsibility for getting the issues addressed properly,
IX,8, Appendix 2	"Pursuant to GCC Clause 6.1.4, if at the time of Contract signing, agreement has not been reached between the Employer and the Contractor, an Adjudicator will be appointed by the Appointing Authority named in the SCC.	To be read as: "Pursuant to GCC Clause 52, if at the time of Contract signing, agreement has not been reached between the Employer and the Contractor, an Adjudicator will be appointed by the Appointing Authority named in the SCC."
IX,16,7	<ul style="list-style-type: none"> • Certificate from OEM of the COTS product for successful implementation 	Deleted
IX, 35, Form 2.1	Performance Security Form (Bank Guarantee)	<p>The following clause is appended to the existing clause</p> <p>Notwithstanding any thing contained herein above Our liability under this bank guarantee shall not exceed Rs____/- (Rupees_____only).</p> <p>This bank guarantee shall be valid up to -----</p> <p>We are liable to pay the guaranteed amount or any part thereof under this bank guarantee only if you serve upon us a written claim or demand (and which should be received by us), on or before-----before14.30 hours (Indian Standard Time) where after it ceases to be ineffect in all respects whether or not the original bank guarantee is returned to us.</p>
IX, 36, Form 2.2	Advance Payment Security Form (Bank Guarantee)	<p>The following clause is appended to the existing clause</p> <p>Notwithstanding any thing contained herein above Our liability under this bank guarantee shall not exceed Rs____/- (Rupees_____only)</p> <p>This bank guarantee shall be valid upto -----</p> <p>We are liable to pay the guaranteed amount or any part thereof under this bank guarantee only if you serve upon us a written claim or demand (and which should be received by us), on or before-----before14.30 hours (Indian Standard Time) where after it ceases to be ineffect in all respects whether or not the original bank guarantee is returned to us.</p>
Ann I, 32, E(c-11)	Request for Transmission arrangement is a manual Process	Deleted.

Ann II, 1, IV	4-way interleaving memory with support for advanced memory protection, including Online spare and Memory mirroring & interleaving.	To be read as : 4-way interleaving memory with support for advanced memory protection, including Fault - tolerance and Memory mirroring & interleaving.
Ann II, 1, V	Should have provision for 8 hard drive bays, expandable to 16 bays.	To be read as: Should have provision for 8 hard drive bays.
Ann II, 1, V	Should have provision for 8 hard drive bays, expandable to 16 bays.	To be read as : Should have provision for 8 hard drive bays.
Ann II, 1, XII	Should have minimum of 8 PCI/PCIe based slots.	To be read as : Should have Minimum 7 No.of PCI / PCIe based slots.
Ann II, 1, XVI	Offer redundant BIOS ROM.	To be read as: Should offer Redundant BIOS ROM or equivalent as per latest chipset architecture.
Ann II, 2, IV	4-way interleaving memory with support for advanced memory protection, including Online spare and Memory mirroring & interleaving.	To be read as: 4-way interleaving memory with support for advanced memory protection, including Fault - tolerance and Memory mirroring & interleaving.
Ann II, 2, V	Should have provision for 8 hard drive bays, expandable to 16 bays.	To be read as: Should have provision for 8 hard drive bays.
Ann II, 2, XII	Should have minimum of 8 PCI/PCIe based slots.	To be read as: Minimum 7 No.of PCI / PCIe based slots.
Ann II, 2, XVI	Offer redundant BIOS ROM.	To be read as: Should offer Redundant BIOS ROM or equivalent as per latest chipset architecture.
Ann II, 2, b)	Should have dual ported 4Gbps Fiber channel HBA	To be read as: 2X Dual ported 4Gbps Fiber Channel HBA.
Ann II, 3, IV	4-way interleaving memory with support for advanced memory protection, including Online spare and Memory mirroring & interleaving.	To be read as: 4-way interleaving memory with support for advanced memory protection, including Fault - tolerance and Memory mirroring & interleaving.
Ann II, 3, XVI	Offer redundant BIOS ROM.	To be read as: Should offer BIOS ROM as per latest chipset architecture.
Ann II, 4, IV	4-way interleaving memory with support for advanced memory protection, including Online spare and Memory mirroring & interleaving.	To be read as: 4-way interleaving memory with support for advanced memory protection, including Fault - tolerance and Memory mirroring & interleaving.
Ann II, 4, V	Should have provision for 8 hard drive bays, expandable to 16 bays.	To be read as: Should have provision for 8 hard drive bays.

Ann II, 4, XII	Should have minimum of 8 PCI/PCIe based slots.	To be read as: Minimum 7 No.of PCI / PCIe based slots.
Ann II, 4, XVI	Offer redundant BIOS ROM.	To be read as: Should offer Redundant BIOS ROM or equivalent as per latest chipset architecture.
Ann II, 4, XXIII	Should have published benchmarks for TPC-c or SAP available.	The following clause is appended to existing clause: If no published benchmark result for the offered server & processor is available then the performance offered by the server will be estimated by linear extrapolation of a published result on a higher server model or a lower server model (with the same processor). If the OEM does not have particular benchmark on a specified server, the OEM can use an Internal benchmark to build the correlation between a benchmark and the proposed Server .The same has to be given in the OEM's letterhead and signed by an authorized person
Ann II,15, III	The storage array should support only Real time / UNIX based operating system, dual, redundant, hot-pluggable; active-active array controllers with high performance RISC based CPUs.	To be read as : The storage array should support only Real time / UNIX or equivalent as per OEM's architecture, with dual, redundant, hot pluggable, active-active array controllers with high performance based CPUs.
Ann II, 15, V	Controllers shall be true active-active so that a single logical unit can be shared across both controllers at the same time	To be read as: Controllers shall be true active-active so that single logical unit can be shared across both controllers.
Ann II, 15, VIII	The storage array should have a minimum of 4GB mirrored cache out of which at-least 1GB usable cache shall be available for write operations.	To be read as: The storage array should have a minimum of 4 GB usable mirrored cache with dynamic cache allocation for read- write operations ensuring optimum performance.



Chief General Manager (S)
MP Power Trading Co Ltd, Jabalpur